

BEREFEX

Outdoor & Indoor Smoothing And Leveling Putty

Description

BEREFEX is a ready-to-use outdoor and indoor putty made of acrylic copolymer resin, fillers & special additives.

BEREFEX is a high quality, easy to use & time saving putty.

Where to use

BEREFEX is used for smoothing and leveling outdoor and indoor walls as well as ceilings prior to the use of emulsion coating.

BEREFEX when applied in several passes may also be used to fill holes and cracks (without any movement) in cement and gypsum plasters.

Advantages

- Good whiteness & non-toxic
- Can be sanded
- Minimal shrinkage
- Excellent workability and ease of use
- Good adherence to smooth substrates e.g. fair face concrete
- Leaves no odor after application.

Properties

Finish Aspect	Matt
Density	1.75 Kg/lit.
% Volume Solids	55% ± 1%
Color's	White

How to use

- Substrate must be clean, sound and free from dust, grease and oil. All loose particles must be removed by mechanical means.
- Absorbent substrates should preferably be moistened with water and sealed with **PROSEALER A**

PROSEALER A

- **BEREFEX** is applied using a knife, plaster trowel or hawk (with no further additions), by sing spray gun (after thinning by water).
- Surfaces must be completely dry between successive coats (minimum 2 hours drying time, according to humidity and temperature)

- In case where more than 3mm layer thickness is required, it is advisable to apply 2 layers within 24 hours or less between each layer (according to temperature).
- Substrates should be sanded and then apply the appropriate paint.
- For exterior application, the substrate should be primed with **PROSEALER A**, then apply a thin layer of **BEREFEX**.

Cleaning:

Clean tools directly after use with water.

Theoretical Coverage:

0.35 - 1 kg/m² according to surface conditions.

Packaging:

20 kg. plastic sacks

Shelf life & Storage:

BEREFEX can be stored for up to 12 months in an original sealed pack within recommended storing conditions (kept away from direct sunlight and high temperature areas)

Health and safety

- Use gloves to avoid contact with skins.
- If skin comes in contact, wash immediately with soap and water.
- Do not use solvents.
- Eye contamination must be immediately washed with water, then seek medical treatment.
- Working areas should be well ventilated.

Additional Information

PROKEM provides the construction industry with a comprehensive range of construction chemicals and specialty products answering the queries of modern engineers for trouble free durable structure.

PROKEM designs tailor made products should there be critical application that requires specific properties rather than our main range.

For our customer's satisfaction, **PROKEM** extends technical services to include after sales support to assist users in a proper handling of our products.