

Name	Sub Group Name	Product Name	Product Description	Complies With
Water Proofing Group	KemSeal (Polymer Modified Cementitious Waterproof)	KemSeal	A two component thixotropic cementitious polymer modified structural waterproof slurry for concrete and masonry.	ASTM C 190, C 580
		KemSeal SF	A two component semi-flexible cementitious polymer modified structural waterproof slurry for concrete and masonry.	ASTM C 190, C 580
		KemSeal F	A two component flexible cementitious polymer modified structural waterproof slurry for concrete and masonry.	ASTM C-190, C-580 Type V, D-413, C-1360, C-541, C50, C-48
		KemSeal BR	A two component thixotropic cementitious polymer modified structural damp-proof protective coating with anti-carbonation properties	ASTM C 190, 580, 882,B117, EN1062-6
		KemSeal Putty	A polymer modified waterproofing mortar form, ready and easy to use by just adding water for smoothing and leveling.	---
		KemSeal VC	A one component waterproofing slurry for concrete based on Vulcapex cement, siliceous graded fillers, additives and a special redispersible polymer.	---
		Crystal Seal	Crystalline waterproofing coating ensures a permanent solution to water leakage or seepage in concrete structures or any cementitious substrate.	ASTM C-39, 78, 1202, 666, 494, 1585, 1012, 579
		BituSeal	Low viscosity cold applied water base bituminous protective coating	ASTM D1227 Type 3, Class 1, AC108, B-79
		BituSeal E	Medium viscosity flexible bitumen base protective coating.	ASTM C-309-93,D1227 Type 3 class 1, D2939
		BituSeal S	Low viscosity cold applied solvent base bituminous protective coating	ASTM C-309-93, D1227 Type 3 class 1, D2939
	KemRoof (Liquid Applied Water Base Bituminous Protective Coating)	KemRoof PA	A 100% solids liquid applied two component polyspartic roof coating.	ASTM D-412, D-2240,D 4060, D-4541, ASTM C-696, C-699
		KemRoof PU	Liquid applied thick polyurethane elastomeric roof coating.	ASTM C-909-96, ASTM D-2240, ASTM D-903, ASTM D-471
		DecaProof	A water base liquid applied one component polyurethane roof coating.	ASTM D-2240,ASTM D- 903,ASTM D-471, ASTM D-412
	Water Plug (Water Plug For Stopping Water Leaks)	Water Plug	Extra Quick Set Hydraulic Cement For Stopping Water Leaks	---
		KemPlug L	A ready to use fast setting liquid hardener for Portland cement mixes.	---
	Pool Coat (Fast Drying Solvent base Chlorinated Rubber Poolcoat)	Pool Coat CR	Fast drying solvent base chlorinated rubber, which contains inert pigments and additives.	ASTM C267, G153, 07867 & D412

Name	Sub Group Name	Product Name	Product Description	Complies With
Epoxy Crack Injection System For Underwater Applications	Release Agent (Release agent)	KemRel O	Oil Based Shutter Release Agent	---
		KemRel W	Water Based Shutter Release Agent	---
	Surface Retardant (Aggregate Concrete Surfaces)	KemRel SC	Powder Release Agent For Stamped Concrete	---
		Prosurface Retardant	A water based top surface retarder which does not require plastic covering for protection.	---
	Curing Agent (Concrete Curing Compound)	KemCure W	Acrylic, Water-based, Concrete Curing Compound	ASTM C309 Type 1,1-d class A or B
		KemCure 30D	Resin-Based, Transparent, Concrete Curing Compound	ASTM C 309 Type 1 or 1-D class A or B

Name	Sub Group Name	Product Name	Product Description	Complies With
Industrial Flooring System	Epoxy Flooring Systems (Flooring that are epoxy based)	KemFloor Metallic	A three component, high performance modified cycloaliphatic epoxy floor coating system.	ASTM D -790, 638, 4541, 4060 & 2240
		KemFloor EA3	Chemical And Abrasion Resistant Solvent Free Epoxy Floor Coating	---
		KemFloor GF	Glass Flakes Reinforced SF-Epoxy flooring	ASTM C-579,C-501, C-836C- 580, C -307
		KemFloor Traffic EP	A fast drying Epoxy-based traffic paint with excellent wearing, UV resistance and weather resistance.	---
	Polyurethane Flooring Systems (Flooring that are PU based)	KemFloor PU	Solvent Free, Flexible, UV resistant Aliphatic Polyurethane Flooring Coat	ASTM C-957, C-1127, C-501, C-836
		KemFloor PUSL	Self Leveling, Hard Wearing Polyurethane Floor Finish, Heat Resistance -40°C, +120°C	---
		KemFloor PUMS	Flexible Solvent-Free Polyurethane Resin Floor Scream	ASTM C109,32,1882
		KemFloor PUSL/AS	Antistatic, MD Polyurethane, Self Leveling Floor System	ANSI ES2, S,7,20,20,DIN 51953 and BS 2050
	Polyspartics Flooring Systems (Flooring that are PA based)	KemPatch PU	A 3 Component Polyurethane patching material with rubber and filler aggregates	ASTM D-2240, D-695, D-471, D-3029 & D-412
		KemFloor PA	High Gloss, High Strength, UV Resistant, Fast Cure, Chemical Resistant, Two Component, Polyspartic Aliphatic Polyurea Coating	---
		KemFloor PA 900	Rapid Curing, Hard Wearing, Abrasion & UV Resistant, Pigmentable, Two Component, Polyspartic Aliphatic Polyurea Floor Coating	ASTM C-905, C-307, D-638, D-2240, D-1593, D-7234, D-4060, D-4541, D-2047, D-968
		KemFloor MSPA	High Strength, Fast Cure, UV- Resistant & Chemical Resistant Polyspartic Floor Scream	ASTM C-349, C-348, D-638, D-4060, D-2048,EN-1582, 1592, 1593, 15901
	Hardners (Floor systems hardners)	KemFloor HF	Non-Metallic, Monolithic Floor For Fresh Concrete Surface Hardener	ASTM D4060,ASTM C 100,ASTM D4541
		KemFloor MF	Metallic Monolithic Floor Hardener	ASTM D4060
		KemFloor SC	Cement Based Concrete Surface Color Hardener	---
		KemFloor VC	Heavy Duty Abrasion And Impact Resistant Floor Topping Non Metallic Monolithic Floor Hardener	---
	KemFloor Aggregates	KemFloor Aggregates	Graded Aggregates For Flooring System	---

Name	Sub Group Name	Product Name	Product Description	Complies With
Protective	Epoxy Protective Coating	Ceramic Coat	100% solids, SF-epoxy resin based product	ASTM D 5499,5895,522
		KemCoat Antistatic	Seamless, Epoxy Based, Anti-Static Wall Coating System	IEC 61340-4-1
		ProSolve EP	Used with epoxy primers and epoxy top coatings for thinning and improve spray characteristics and film appearance	---
		KemCoat GF	A solvent free, anne cured epoxy coating reinforced with glass flakes	ASTM B 117, D4541
	Oil Based Protective Coating	KemCoat CR	A hard wearing chemical resistant finish coat. It can be applied on plastic, cement, concrete, steel and wood.	ASTM C267, G153, 07867 and D412
		KemCoat ALU	An aluminum finish coat for steel structures that is based on alkyl oil.	---
		KemLac	A high gloss modified alkyl finishing coat suitable for both interior and exterior steel and wood works.	ASTM 2697
	Polyurethane Protective Coating	KemCoat PU	Solvent – Free, Flexible, Aliphatic Polyurethane Finishing Coat	ASTM C267, D5895, 522, 4587, G153, 154
		Prothan TC	Two components aliphatic polyurethane used as a top coat with gloss and color retention.	ASTM B117,D4541,G154
		KemPutty PU	A 2 component polyester polyurethane resin based, resilient & SF mastic for rubber floors and other surfaces	---
	Polyspartics Protective Coating	ProSolve PU	It's a high purity solvent blend for thinning polyurethane based coatings.	---
		KemCoat PU EP	A solvent free two components thixotropic flexible polyurethane/epoxy coating (transparent or colors)	---
	Acrylic Protective Coating	KemCoat PA	High Gloss, High Strength, UV Resistant, Fast Cure, Chemical Resistant, Two Component, Polyspartic Aliphatic Polyurea Coating	ASTM D 1308
		Procoat AC	High Quality Emulsion Anti-Carbonation Decorative Coat based on acrylic co-polymer	BS EN 1928
	Poly Urea Coating	Decacoat W	Anti-Carbonation, Weather and Waterproof Micro Polymer Exterior Protective and Decorative Coating	ASTM D4541
		Kem Poly Urea 100	Liquid Applied Pure Poly Urea (PU)	EN 13501-1-2002

Name	Sub Group Name	Product Name	Product Description	Complies With
Repair and Corrosion Inhibitor	Corrobond (Anti-Corrosive Cement-Base, Polymer Modified Repair Coating & Bonding Agent)	Corrobond 100	100% solids 3 components system of anti-corrosive, protective, bonding & repair epoxy-cement mortar	---
		Corrobond 101	An anti-corrosive, cement-base polymer modified repair coating & bonding agent between old & new concrete.	---
	KemKleen (Densitizing & Passivating Liquid For Metallic Surfaces)	PCI 1010	A single-component, clear liquid applied corrosion inhibitor with a mild odor.	ASTM C-109,B117
		KEMKleen	Densitizing & passivating liquid for metallic surfaces.	---
	Epoxy Adhesive (Adhesive For Bonding)	Epoxy Adhesive CFT	Epoxy Adhesive For Carbon Fiber Textile	---
		Epoxy Adhesive CFL	Adhesive For Bonding Carbon Fiber Laminates	---
		CarboComb Textile 225	Unidirectional carbon fiber textile with carbon fibers in the longitudinal direction.	---
		CarboComb Textile 300	Unidirectional carbon fiber textile with carbon fibers in the longitudinal direction.	---
	KemRepair (High Strength Polymer Modified Non-shrink Repair Mortar)	KemRepair	High Strength Polymer Modified Non-shrink Repair Mortar	---
		KemRepair F	High Strength Fiber Polymer Modified Non-Shrink Concrete Repair Mortar	---
		KemRepair 2F	High Strength Fiber Polymer Modified Non-Shrink Two Component Repair Mortar	---
		KemRepair FC	Cement-base, singlecomponent, polymer modified silica fume containing, moisture resistant, and surface applied mortar	---
		KemRepair L	Light Weight Polymer Modified Non Shrink Repair Mortar	---
		KemRepair VC	A Shrinkage Compensating, Non-Sag, Cement-Base Repair Mortar	---
		KemRepair EP	High Strength Epoxy Repair Mortar	---



Name	Sub Group Name	Product Name	Product Description	Complies With
Heat, Acoustic and Radiation Insulation	Perrite Mortar Protection	Properl Plaster	High Quality Plaster For Sound Absorption, Thermal Insulation & Fire Proofing	ASTM C-423
		Properl Crete	Perrite concrete aggregates combined with portland cement and water to produce a lightweight concrete insulation layer	ASTM C-332
		Properl Loose	Cementitious, Inorganic, Fireproofing Plaster	ASTM C-332
	Thermody (Thermal insulation)	Properl Insulation	Loose Fill Perrite Insulation	ASTM C-549, C-520, C-1363-E-84
		Decacoat W Thermody	An acrylic membrane coating with thermal insulating properties, ideal for both interior and interior use	ASTM D 5957, 412, 471, 2369
		Decaproof Thermody	Liquid Applied Polyurethane Elastomeric And Thermal Insulating Roof Coating	ASTM D-412, 903, 471, 5957
		KemRoof PU Thermody	A 100% solids liquid applied two component polyurethane coating, fast cure waterproofing elastomeric coating	---
		Procoat Thermody	High Quality Emulsion Decorative Thermal Insulating Paint	ASTM D412, 471, 5441, EN12667
		KemFloor PA Thermody	High Gloss, High Strength, UV Resistant, Fast Cure, Chemical Resistant, Thermal Insulating, Two Component, Polyspartic Aliphatic Polyurea Coating	ASTM E96, D638, 4060, 5441, EN12667
		KemFloor MS EP Thermody	Heavy Duty, Thermal Insulation Epoxy Resin mortar Floor Scream	ASTM BS EN12667
		KemRoof PA Thermody	Liquid Applied Polyspartic, Weather & UV Resistant, Fast Cure Elastomeric Roof Coating	ASTM C-836-836M/15
	Antradiation	Proplaster Antradiation	It is a radiation shield plaster for brick, concrete floor, walls, ceilings with consistency of 2mm.	EN DIN 6812

Name	Sub Group Name	Product Name	Product Description	Complies With
Joining and Tiling	KemTile (Cement/Acrylic /Epoxy Tile Adhesives)	KemTile A	Acrylic-Base Tile Adhesive For In/Outdoor (Type D, Class T2)	EN 12004 (Type D, Class T2)
		KemTile C	Cement Base Ceramic Floor & Wall Tile Adhesive (Type C, Class T2)	EN 12004, ANSI A118.4
		KemTile Fix	Standard Cement Based Tile Adhesive EN 12004/Type C, Class T2	EN 12004 (Type C, Class T2)
		KemTile Fix Flex	Cement Based, High Flexibility Tie Adhesive EN12004 (Type C, Class T2)	EN12004, EN1348, Type C, Class T2
		KemTile AR	Halogen-Free Acid Proof Cement	---
		KemTile UW	Epoxy Adhesive For Carbon Fiber Textile	EN 12004 Type R, Class T2
	Adhesive (Adhesive for floors, rubber or wood)	KemTile E	Two component solvent free, non sag epoxy paste suitable for bonding cement, stone & ceramic	EN 12004 Type R, Class T2
		Novolac	A 3 components epoxy system developed for use in conditions where high degree of hygiene is important.	EN 12004, EN13880, ANSI A118.7, EN12808-2,3,5
		Epoxy Adhesive	Three Component, Solvent Free, Epoxy Novolac Adhesive For Ceramic Floor & Wall	---
		Polyurethane Adhesive	A solvent free epoxy floor covering adhesive with a high initial tack	---
	KemJoint (Cement/Acrylic /Epoxy Jointing Compound)	KemJoint C	A solvent free, two component polyurethane adhesive, trowel-grade, waterproof	EN 12004, EN13888, ANSI A118.3
		KemJoint E	A 3 components epoxy system developed for use in conditions where high degree of hygiene is important.	EN 12004, EN13880, ANSI A118.7, EN12808-2,3,5
		KemJoint E	Cement Base Grouting Mortar For Sealing Pores And Shrinkage Cracks In Mortar Joints Of Bricks And Tiles	---
		Novolac Flexijoint	A 3 component epoxy novolac system developed for use in conditions where high degree of hygiene is important.	---
	Proflex (Polyurethane/Silicon Joint Sealant)	Proflex	A 2 components joint sealant based on a modified combination of coal tar-pitch epoxy system and special filler.	ASTM D698, C882, 1247,48
		Proflex LM	A joint sealing system composed of two products for joints and cracks.	---
		Proflex LM Pro	A Versatile, One Component, Low Modulus, Silly-Terminated Polyurethane Sealant	---
		Proflex PU2	A Versatile, One Component, Low Modulus, Silly-Terminated Polyurethane Sealant	ASTM C920 type M grade P class 25
		Proflex PU2-T	A two component polyurethane sealant that is pourable, cold applied & contains no pitch or tar	ASTM C-920 Type M grade P class 25
		Proflex SL	Two Component, Jet Fuel Resistant, Polyurethane Tar Sealant.	ASTM C920, Type S, Grade P, Class 25
		Proflex NS	One Component, Neutral Curing Silicone Rubber Sealant.	ASTM C-920 Type S, Grade NS, Class 25
		Proflex NSS	Fire Rated One Part Silicon Rubber Sealant	ASTMC -920 class 25
		Proflex MS	High Performance, Weather-Proofing Sealant & Adhesive Based on Modified Silicone	ASTM C-719, C-714, D-412, D-2240 ASTM C360 class 25

Name	Sub Group Name	Product Name	Product Description	Complies With
Bonding Agents	Acrylic Bonding Agent (Non re-embellishable, acrylic latex bonding agent)	KemCure W 101	Acrylic, Water-based, Concrete Curing Compound	ASTM C309 Type 2 Class B or A
		KemBond A	A non re-emulsifiable, acrylic latex bonding agent and admixture.	ASTM C 1059 TYPE II
	Epoxy Bonding Agent (Epoxy Resin New To Old Concrete Bonding Agent)	KemBond EP	A two-components epoxy adhesive based on selected solvent free epoxy system and formulated with special pigments and fillers.	ASTM 881-78 type II, grade 2 class B+C
		KemBond SBR	Styrene butadiene co-polymer emulsion for use as a primer, bonding agent and admixture to cement to improve water-resistance, adhesion strength and long-term durability.	ASTM C 1059 TYPE II
	Styrene Butadiene Polymer Bonding Admixture	KemBond LX	Styrene-butadiene copolymer specially designed for use as bonding admixture for cementitious systems.	ASTM C1059 TYPE II
		KemLatex SBR	Styrene-butadiene resin which imparts beneficial property improvements to cementitious mixes.	ASTM C 1059 type II

Name	Sub Group Name	Product Name	Product Description	Complies With
Sports Flooring	Hard Flooring Acrylic	Prodeco S	An Acrylic Resurfaces With Sand For Filling And Smoothing Sport Floors & Plaster	---
		Prodeco P	A Fast drying acrylic based coating provides concrete and asphalt floors with excellent resistance against abrasion, wear and weather conditions including UV-resistance.	---
	Soft Flooring Acrylic	Prodeco Cushioned	Base & Secondary Cushion Layers For Sport Floors	F2772, 1242, D624, EN12235, 1569, 15501, 1516
		KemTrack	It is a mix of acrylic emulsion with graded granular rubber particles designed to impart excellent flexibility to concrete or asphalt running tracks and sports flooring.	---
	Hard Flooring Polyurethane	Prodeco S/PU	A Polyurethane Decorative, Waterproofing,Texture Plaster & Putty For Concrete	---
		Prodeco P/PU	A 100% PU based coating provides concrete, asphalt & sport floors with excellent resistance against abrasion, wear and weather conditions including UV-resistance.	---
	Soft Flooring Polyurethane	Prodeco PU Cushioned	Base & Secondary Cushion Layers For Sport Floors Based On Polyurethane Binder & Rubber.	ASTM F2772, 1242, D624, EN12235, 1569, 15501, 1516, 1517

Name	Sub Group Name	Product Name	Product Description	Complies With
Decorative	Primers (Decorative Primers)	Prosealer A	n/Outdoors Acrylic Polymer Sealer With Special Additives	---
		Sealer AC	Tinted Acrylic Emulsion Sealer For Protecting Concrete And Masonry Surfaces	---
		Bonding Primer	Primer For Water Based & Epoxy Coating	---
		DECACOAT W/PUTTY	Outdoor & Indoor acrylic co-polymer paint and crack filling putty	---
	Acrylic Base	Berefex	Outdoor and indoor putty made of acrylic copolymer resin, fillers & special additives	---
		Berefex Flex	Outdoor & Indoor acrylic co-polymer paint and crack filling putty	---
		Inplast 101	Interior emulsion acrylic paint with the highest quality, superior non-yellowing to conventional paints, outstanding resistance, longer life expectancy	---
		Inplast 102	Acrylic Matt emulsion decorative indoor paint, with a very good flat smooth durable surface	---
		Inplast 103	An Economic emulsion interior finish paint based on acrylic copolymer, giving a uniform smooth Matt appearance	---
		Prosova Plaster	An Acrylic Elastic Structured Fibred Plaster	---
	Cementitious Base	Procoat	A top quality exterior emulsion paint based on acrylic resin with high hiding power	---
		Prostone Plaster	Natural Lime Stone Veneer Plaster	ASTM C106, C-348, C-190,D6970-2,D670-02,E-96,BS 139-34
		Proviato	Decorative Texture Finishing For Concrete And Plastering	---
		Protex	An Economic Acrylic range-mixed textured coating (fine, medium coarse)	---
		Cement Putty	Non-Shrink Cosmetic Cementitious Putty For Concrete Surface (fine & coarse)	---
		KEMSEAL MORTAR / VC	High Performance Cement-Base Water Proofing Cementitious Lining	---
	Water Base	Plaster Mix	High Quality Premixed Cement Finishing Plaster	---
		Profinish	A high quality cement based, fine smooth or texture finish coat and plaster	---
		Proplaster	Cement Based, Polymer Modified, Spatter Dash	---
		Prostucco	A Cement Based External Decorative Finishes	---
Fabrics	Water Based	Kleer G - WB	Water-Based Water Repellent / Damp-Proof Course	---
		Stericoat	A resin rich water-based fungic static protective and decorative finish	---
	Fabrics	Fibermesh	A fiber glass fabric coated by the acrylic acid copolymer liquid	ASTM E-2098
		Kemfelt PP	A Polypropylene continuous filament needle-punched non-woven geotextile.	---
	Mineral Admixture	Kemfelt EG	A Woven Glass Fiber Fabric	---

Name	Sub Group Name	Product Name	Product Description	Complies With
Grouts and Anchoring	KemGrip (Thixotropic Three Components Solvent Free Epoxy Resin Anchoring)	KemGrip EP	Thixotropic Three Components Solvent Free Epoxy Resin Anchoring	ASTM C-881 Type IV, Grade 3 Class B.C
		KemGrip EP2	Thixotropic Three Components Solvent Free Epoxy Resin Anchoring	ASTM C881 Type V, Grade 3 Class B.C BS C900:488
		KemGrip E65	Thixotropic Two Components Solvent – Free Epoxy Resin Anchoring & Concrete Repair	ASTM C881, BS EN 12004, A54, E18
		KemGROUT EP	A solvent free, 3 component epoxy resin based product designed for Non-shrink, free flow grouting of gap width from 10mm.	---
	KemGrout (High Performance Non Shrink Grout)	KemGrout HD	High Performance Expanding Non-Shrink Cementitious Grout	ASTM C1107 Grade B or C
		KemGrout HD-F	High Performance Expanding Non-Shrink, Fiber Reinforced Cementitious Grout	ASTM C1107 Grade B or C
		KemGrout UW	Underwater Cement Base Grout	BS 1881
		KemGrout AID UW	Anti-washout admixture based on cellulose based material with thixotropic agents and super plasticizers	BS8443:2005
		KemGrout AID	Powder admixture for cement grouts and concrete, combining a plasticizing agent and a gas producing expansion medium.	ASTM C827
		KemGrout MC	A free-flowing, one component, cement based micro-concrete modified with aggregate, fillers, micro silica and other selected additives.	ASTM C580, 191, C230
	KemInject (Solvent Free Injection)	KemInject EP	A solvent free, two component low viscosity epoxy resin with a modified cycloaliphatic amine hardener.	DIN 53452, DIN 53455,DIN53453, DIN53483, DIN 53475
		KemInject PU	A nonflammable, solvent free, two components polyurethane foaming injection material.	ASTM C-1107 759-94C-1042-1994, C-1059-94
KemInject VC		One Component Cementitious Injection Grout To Stop Seepage Through Concrete And Masonry By Filling And Sealing Cracks And Leaks	---	
KemInject WB		Water-Based Water Repellent / Innovative Silicate Resin	---	
	KemInject UW	Epoxy Crack Injection System For Underwater Applications	ASTM C-881, Type II grade I, Class B.C	