

Inplast 102

High Quality Washable Emulsion Interior Paint

Description	Inplast 102 is an acrylic Matt emulsion decorative indoor paint, with a very good flat smooth durable surface.
Where to use	<ul style="list-style-type: none"> • Inplast 102 is used for interior applications on old plaster as well as new plaster, concrete, wood and old emulsion paint.
Advantages	<ul style="list-style-type: none"> • Durable excellent protection. • Excellent Color stability & waterproof. • Gives a very good flat smooth durable surface. • Economic, easy to apply & non yellowing. • Easy to maintain.
Properties	
Finish Aspect	Matt
Specific Gravity	1.45 - 1.50
Drying time	3-4 hours @ 23 °C
Dry to recoat	5-6 hours @ 23 °C
% Volume Solids	60-65%
Color's	White and a high range of Color's available.
Surface Preparation	<ul style="list-style-type: none"> • Surfaces must be free from dust, grease and oil stains. • Surface must be primed with Prosealer A. • Fill cavities and cracks with Berefex then use Berefex to level the surface. • Surfaces has to be sanded before painting.
Application	<ul style="list-style-type: none"> • Mix the product in its container thoroughly manually or mechanically to get a uniform color. • Emulsion must be mixed before use and surfaces should be sanded. • Apply using brush, roller. Spray gun can also be used.
Theoretical Coverage	0.2 Kg/m ² at 85 microns D.F.T Minimum of 2 coats are required
Packaging	5 & 20 Kg plastic pails
Shelf life & Storage	Storage can reach 12 months in a day place, away from direct sunlight and high temperatures.
Health and Safety	<ul style="list-style-type: none"> • Use gloves to avoid contact with skins. • If skin comes in contact, wash immediately with soap and water. • Do not use solvents. • Eye contamination must be immediately washed with water, then seek medical treatment. • Working areas should be well ventilated.
Additional Information	<p>PROKEM provides the construction industry with a comprehensive range of construction chemicals and specialty products answering the queries of modern engineers for trouble free durable structure.</p> <p>PROKEM designs tailor made products should there be critical application that requires specific properties rather than our main range. For our customer's satisfaction PROKEM reserves the right to change the properties of its products.</p> <p>All orders are accepted subject to our current term of sale & delivery.</p> <p>Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request.</p> <p>PROKEM extends technical services to include after sales support to assist users in</p>