

Procoat AC

High Quality Emulsion Anti-Carbonation Decorative Coat

Description	<p>Procoat AC is a top quality exterior emulsion anti-carbonation coat based on acrylic co-polymer with high hiding power. Procoat AC has been designed to give a high quality protective and decorative effects, and to be applied directly on most building materials for new or old maintenance applications.</p> <p>It is used for both interior luxury finishes and exterior finishes.</p>
Where to use	<ul style="list-style-type: none"> • For high quality indoor and outdoor applications. • Can be painted over plaster, fair-faced concrete rigid PVC, wood, metals (with the suitable primer). • Old compatible paint and many other services. • Excellent for indoor and outdoor applications necessitating wet abrasion (high wash ability resistance)
Advantages	<ul style="list-style-type: none"> • High covering power and opacity. • Excellent wet abrasion (wash ability) resistance. • Exceptional resistance to extreme weather conditions (humidity, rain, hot, temperatures, sea-shores conditions, UV rays, and pollution) • High resistance to cracking, peeling and chalking. • Non yellowing white. • Easy to use. • Anti-Carbonation (Low diffusion of CO₂ & Chlorides). • Resist air born gases & dust from sticking. • Resist fuel & oil fumes & splashes.
Properties	
Density	1.50 ±0.2 Kg/L
Drying Time	4 - 6 hours
Tensile St.	1.8 - 1.9 N/mm ²
Elongation	10 - 11 %
Full curing	7 Days
Recoating Time	10 - 12 Hours
% Volume Solids	60 ±5 %
Carbon dioxide diffusion D.F.T 300 micron	4.84*10 ⁵ (115.2 m)
Water vapor transmission	3.21 g/m ² .Day
Water permeability	115.7 g/m ² .Day
Bond Strength	1.31 N/mm ²
Crack bridging	0.5 mm
It complies with ASTM D-41 2, D-4 060, C-13 05, E-96, EN 1062	
Resistance to 1 m. column water pressure show no leak (BS EN 1928)	
Surface Preparation	Surface must be clean, free from oil, grease, dirt, chalk, loose paint and other foreign materials.
Application	<ul style="list-style-type: none"> • Apply one coat (or more) of Prosealer A according to the surface porosity. • Apply an acrylic putty to smoothen the surface and fill the voids and gaps with Berefex flex followed by sanding. • Mix Procoat AC thoroughly to uniform consistency before use, and dilute 20% with water for priming purpose & 10% for finishing coats. • Application is done by brush, roller or airless spray gun. • Application temperature +5/+30 °C.
Theoretical Coverage	0.2 Kg / m ² @ 80-micron D.F.T 2 coats are recommended
Packaging	5 & 20 Kg pails
Shelf life & Storage	12 months in original tightly closed containers away from sunlight and excessive heat.

Health and Safety

- Use gloves to avoid contact with skins.
- If skin comes in contact, wash immediately with soap and water.
- Do not use solvents.
- Eye contamination must be immediately washed with water, then seek medical treatment.
- Working areas should be well ventilated.

Additional Information

PROKEM provides the construction industry with a comprehensive range of construction chemicals and specialty products answering the queries of modern engineers for trouble free durable structure.

PROKEM designs tailor made products should there be critical application that requires specific properties rather than our main range. For our customer's satisfaction,

PROKEM reserves the right to change the properties of its products.

All orders are accepted subject to our current term of sale & delivery.

Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request.

PROKEM extends technical services to include after sales support to assist users in a proper handling of our products.
