

Kemfloor Traffic / EP

Epoxy-Based Traffic Paint

Description	It is a fast drying epoxy-based traffic paint with excellent wearing, UV resistance and weather resistance.
Where to use	It designed to be used as a traffic paint and as an exterior coating for: <ul style="list-style-type: none"> •Concrete sidewalks. •Decks. •Roads and Courts. •Asphalt and Wood.
Advantages	Easy to be applied by brush or roller on asphalt and cementitious surfaces with a very good flow giving a smooth appearance resistant to water and sea water. It has an excellent durability to atmospheric conditions. Good resistance to mild chemicals. Very good color retention.
Properties	
Color	Upon request
Mass Density Approximately	1.5 Kg/m ³
Solids Content	100% by volume
Dry Film Thickness	100 microns / coat
Touch Dry	60 - 80 minutes @25 °C
Hard Dry	24 hours @25 °C
Surface Preparation	Surfaces must be clean from dust, dirt, debris and loose material.
Mixing	Stir the material (A & B) in its container and mix thoroughly before use.
Application	Apply the material with brush or roller. Apply 2 – 3 coats with time between coats up to 60 minutes. Leave to dry for a 24 hours.
Cleaning	Clean all tools immediately after work with solvent (Prosolve EP).
Theoretical coverage	0.15 Kg/m ² for 100 micron
Packaging	1 Kg cans (A&B) 5 Kg cans (A&B)
Shelf life & Storage	One year in its original cans stored at the suitable conditions.
Health and Safety	Use goggles, Gloves and breathing mask when applying. Applied forced ventilation in confined spaces. Skin splashes to be removed with hand cleaner, soap and water. Eye splashes to be washed with plenty of water. If ingested seek medical advice.
Additional Information	PROKEM provides the construction industry with a comprehensive range of construction chemicals and specialty products answering the queries of modern engineers for trouble free durable structure. PROKEM designs tailor made products should there be critical application that requires specific properties rather than our main range. For our customer's satisfaction. PROKEM reserves the right to change the properties of its products. All orders are accepted subject to our current term of sale & delivery. Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request. PROKEM extends technical services to include after sales support to assist users in a proper handling of our product.