

Prosolve PA

Polyaspartic Thinner

Description	It can be used for thinning Polyaspartic based coatings. It is used for thinning and improving spray characteristics and film appearance.
Where to use	<ul style="list-style-type: none"> • For thinning Polyaspartic coats. • It is an excellent cleaner for rollers, brushes, and spray tools in contact with Polyaspartic coatings.
Advantages	<ul style="list-style-type: none"> • Improve spray characteristics. • Compatible with Polyaspartic coats. • Can be used in all environments including high temp. & R.H
Properties	
Color	Clear
Specific gravity	0.89
Flash point	27 °C
How to use	<ul style="list-style-type: none"> • The Solvent should be stirred thoroughly and allowed to stand. • All air bubbles must be allowed to disperse before spraying. • The solvent should be added gradually until the coating pattern and weight are achieved. • If the solvent evaporates with time, the loss must be replaced to maintain the required viscosity. • Do not add more than 5% of the volume to Polyaspartic coats • Recommended application conditions are: • R.H.: 20 – 90 % • It is flammable, it must be used in well ventilated areas, away from ignition.
Packaging	4 Kg Drums 18 Kg Drums 180 Kg Drums
Shelf Life & Storage	24 months in its original unopened packs stored at ambient conditions
Health and Safety	<ul style="list-style-type: none"> • Prosolve PA is non-toxic. Any splashes to the skin should be washed immediately with water. • Splashes to the eyes should be washed immediately with water and medical advice should be sought.
Additional Information	<p>PROKEM provides the construction industry with a comprehensive range of construction chemicals and specialty products answering the queries of modern engineers for trouble free durable structure.</p> <p>PROKEM designs tailor made products should there be critical application that requires specific properties rather than our main range for our customer's satisfaction.</p> <p>PROKEM reserves the right to change the properties of its products.</p> <p>All orders are accepted subject to our current term of sale & delivery.</p> <p>Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request.</p> <p>PROKEM extends technical services to include after-sales support to assist users in the proper handling of our products.</p>