

Procoat

High Quality Emulsion Decorative Paint

Description	<p>Procoat is a top quality exterior emulsion paint based on acrylic resin with high hiding power</p> <p>Procoat has been designed to give a high quality protective and decorative effects, and to be applied directly on most building materials for new or old maintenance applications.</p> <p>It is used for both interior luxury finishes and exterior finishes.</p>
Where to use	<ul style="list-style-type: none"> • For high quality indoor and outdoor applications. • Can be painted over plaster, fair faced concrete rigid PVC, wood, metals (with the suitable primer) • Old compatible paint and many other services. • Excellent for indoor and outdoor applications necessitating wet abrasion (high wash ability resistance)
Advantages	<ul style="list-style-type: none"> • Gives a Matt flat finish. • High covering power and opacity. • Excellent wet abrasion (wash ability) resistance. • Exceptional resistance to extreme weather conditions (humidity, rain, hot, temperatures, sea-shores conditions, UV rays, and pollution) • High resistance to cracking, peeling and chalking. • Non yellowing white. • Easy to use, non-flammable, environmentally friendly & low odor. • Will not support fungal & bacterial growth.
Properties	
Specific Gravity	1.50 Kg/L
Drying time	30 - 60 min. @ 23 °C
Tensile	1.9 N/mm ²
Elongation	9.7 %
Water Absorption	1.97 %
Full curing	Within 7 days
Recoating Time	5 - 6 Hours
% Volume Solids	60 %
Surface Preparation	Surfaces must be clean, sound, and free from dirt, grease and loose particles.
Mixing	Mix Procoat thoroughly to uniform consistency before use.
Application	<ul style="list-style-type: none"> • Apply one coat (or more) of Prosealer A according to the surface porosity. • Apply an acrylic putty to smoothen the surface and fill the voids and gaps with Brefex followed by sanding. • Application is done by brush, roller or airless spray gun. • Minimum two coats are to be applied.
Cleaning	Clean tools directly after use with water.
Theoretical Coverage	0.2 Kg/m ² at 80 microns D.F.T Minimum of 2 coats are required
Packaging	5 Kg plastic bags 20 Kg plastic bags
Shelf life & Storage	Procoat can be stored for up to 12 months in an original sealed pack within recommended storing conditions (kept away from direct sunlight and high temperature areas)

Health and Safety

Use gloves to avoid contact with skins.
If skin comes in contact, wash immediately with soap and water.
Do not use solvents.
Eye contamination must be immediately washed with water, then seek medical treatment.
Working areas should be well ventilated.

Additional Information

PROKEM provides the construction industry with a comprehensive range of construction chemicals and specialty products answering the queries of modern engineers for trouble free durable structure.
PROKEM designs tailor made products should there be critical application that requires specific properties rather than our main range. For our customer's satisfaction, **PROKEM** reserves the right to change the properties of its products.
All orders are accepted subject to our current term of sale & delivery.
Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request.
PROKEM extends technical services to include after sales support to assist users in a proper handling of our products.