

Proplaster

Cement Based, Polymer Modified Spatter Dash

Description	It is a cement based, ready mixed, polymer modified mortar requires only the addition of water on site. It is a mixture of cement ,graded fillers and special additives
Where to use	<ul style="list-style-type: none"> • Scratch coat Spatter Dash mortar on fair faced concrete. • cosmetic repairs. • Outdoor spatter Dash final finish plaster.
Advantages	<ul style="list-style-type: none"> • Excellent bonding. • High water resistant. • Weather resistant. • Easy to apply.
Properties	
Color	Grey
Form	Powder
Density	1.7 ±0.1 Kg/L
Pot life @ 23 °C	30 minutes
Bond Strength	>0.5 N/mm ²
Compressive Strength	>5 N/mm ² after 28 days
Surface Preparation	<ul style="list-style-type: none"> • All surfaces as fair concrete, brick and blocks. shall be sound and clean • Surface must be free form loose particles. dust and oils,
Mixing	<ul style="list-style-type: none"> • Mix the powder with clean water. • Mix with hand drill or manually for small amounts • Add (4.5 - 5 L) of clean water into container then add the powder (30 Kg) gradually and mix until a uniform mortar is obtained.
Application	<ul style="list-style-type: none"> • Apply the mortar in spatter dash from at 5 mm thickness. • Use spray or manually to produce a rough surface. • Cure for 24 hrs. .by water spraying (twice / day) • Wash with water before plastering
Theoretical Coverage	5 – 8.5 Kg/m ² for 3mm - 5mm thickness
Packaging	15 Kg Sacks
Shelf life & Storage	One year in its unopened packs stored in appropriate conditions
Health and Safety	<ul style="list-style-type: none"> • Proplaster is nontoxic. • Use gloves to avoid contact with skins. • If skin comes in contact, wash immediately with soap and water. • Do not use solvents. • Eye contamination must be immediately washed with water, then seek medical treatment.
Additional Information	<p>PROKEM provides the construction industry with a comprehensive range of construction chemicals and specialty products answering the queries of modern engineers for trouble free durable structure.</p> <p>PROKEM designs tailor made products should there be critical application that requires specific properties rather than our main range. For our customer's satisfaction, PROKEM reserves the right to change the properties of its products.</p> <p>All orders are accepted subject to our current term of sale & delivery.</p> <p>Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request.</p> <p>PROKEM extends technical services to include after sales support to assist users in a proper handling of our products.</p>