

Proviato

Decorative Texture Finishing for Concrete and Plastering

Description	<p>Proviato is an acrylic– based decorative, texture coating for concrete and plastered surfaces, It becomes a part of the substrate.</p> <p>Proviato comes in a ready form to apply a uniform decorative coating that possesses a high density, great durability, hardness, and nice shape preferred by all architect engineers.</p>	
Where to use	<ul style="list-style-type: none"> • It is used for interior and exterior plastering • On all kinds of cement rendering, concrete, gypsum substrates • Pre-cast concrete surfaces • Bricks and natural stones 	
Advantages	<ul style="list-style-type: none"> • A heavy base acrylic coating, not a thin paint film • UV and weather resistant • Protects surfaces with a decorative and durable finish • Washable and waterproof • Fills and seals holes and voids from marks and honeycombs • Provides surface integrity • Maintains architectural details of fluting vertical lines and grooves • Can be used for decorative moldings • Hides all flaws and plastering faults • Excellent aging and salt spray resistance • Three different grades to cover all surface requirements 	
Properties		
Density	1.8 ±0.2	
Appearance	Colored paste	
Solid content by volume	80 - 83 %	
Adhesion	Excellent	
Fungus resistance	Excellent	
U.V. resistance	Excellent	
Coating – Salt Spray resistance	No cracking, no flaking, no blistering, no spot rusting was observed	Satisfactory – ASTM B117-18
Surface Preparation	<ul style="list-style-type: none"> • Concrete to receive Proviato should be carefully formed to provide a smooth surface, free of form marks and in good condition • Remove all traces of form release materials and curing compounds • Plastered walls to receive Proviato should be in good condition, properly cured, laid true and free of efflorescence • fill all honeycombed areas that are 1 cm or more in depth with a suitable material from Kemrepair range • Remove all concrete appurtenances that extend above the level of the surface by use of a mortar hoe, stone or grinding 	
Trowel and float finish	<ul style="list-style-type: none"> • Mix in sufficient quantities so that the mixture has a consistency suitable for application by trowel • Power mixing is preferred • Apply a primer coat of Prosealer A prior the application of Proviato • The workman should follow with a trowel, the surface should be textured uniformly in one direction 	

Cleaning	Clean all the equipment's with water immediately after use
Theoretical Coverage	Soft Coarse: 2 - 3 Kg/m ² Medium Coarse: 3 - 4 Kg/m ² Hard Coarse: 4 - 5 Kg/m ² coverage changes according to thickness, texture and surface conditions
Packaging	20 Kg Sacks
Shelf life & Storage	It has a shelf life of 12 months if kept in original packaging in a dry condition
Health and Safety	<ul style="list-style-type: none"> • This product is non-toxic but normal precautions should be observed • Wear hard gloves and tight goggles • Wash off any skin splashes with fresh water • Irrigating the eye with an eye bathing solution should treat eye contamination • Ensure adequate ventilation in confined spaces and use breathing aids • If ingested, drink milk or water and seek medical attention • In cured state the product is not known to cause an adverse environmental effect
Additional Information	<p>PROKEM provides the construction industry with a comprehensive range of construction chemicals and specialty products answering the queries of modern engineers for trouble free durable structure</p> <p>PROKEM designs tailor made products should there be critical application that requires specific properties rather than our main range. For our customer's satisfaction, PROKEM reserves the right to change the properties of its products</p> <p>All orders are accepted subject to our current term of sale & delivery Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request</p> <p>PROKEM extends technical services to include after sales support to assist users in a proper handling of our products</p>